

Product data sheet Perlan 140 KS wood



Corrosion-resistant sliding door fitting system for wood, plastic, or metal elements with a leaf weight of 140 kg

AREAS OF APPLICATION

- ightarrow Corrosion-resistant fitting for exterior use
- ightarrow Sliding shutters and shading systems
- ightarrow Installation of fittings possible in combination with overhanging weather hood
- ightarrow Single and multi-leaf sliding panel
- ightarrow Mounting to the wall and also to the ceiling via additional ceiling brackets

Product data sheet | Page 2 of 5 Perlan 140 KS wood



PRODUCT FEATURES

- ightarrow Extremely reliable corrosion protection for leaf weights up to 140 kg
- \rightarrow Tested in accordance with EN 1670 Class 4 for external use or in extreme climatic conditions, such as swimming baths
- ightarrow For leaves made of wood, plastic, or metal
- ightarrow Precision ball bearings in the roller carriages offer very smooth sliding action

TECHNICAL DATA

Productname

Perlan 140 KS wood

PART

TRACK PERLAN 140

Track for sliding door fitting



Designation	Description	Ident-No.	Colour
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135061	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135050	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135049	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1

Product data sheet | Page 3 of 5 Perlan 140 KS wood

ACCESSORIES

HOLD-OPEN SPRING

Hold-open spring for Perlan 140 end stop

Designation	Ident-No.
Hold-open spring	064242

DOOR STOP

End stop for sliding leaves

Designation	Ident-No.
Door stop	000339
Door stop	000342

CLAMPING INSERT, GLASS CLAMPING PLATE 30 MM *

Clamping shim for glass thicknesses of 12.76 mm (1/2 inch)

Designation	Description	Ident-No.
Clamping insert, glass clamping plate 30 mm	for 2 glass clamping plates, for use with 12.7 mm (1/2 inch) toughened safety glass	142634









Product data sheet | Page 4 of 5 Perlan 140 KS wood

HEIGHT COMPENSATION MECHANISM / CEILING DISTANCE SET, WITH VARIABLE ADJUSTMENT

Height compensation with variable adjustment for ceiling installation of tracks

Designation	Description	ldent- No.
Height compensation mechanism / ceiling distance set, with variable adjustment	6 pieces, height compensation mechanism with variable adjustment from 13 mm to 18 mm. For use for ceiling mounting using clip-on cover 100/145 as well as for general use on uneven ceilings	138099

ALL-GLASS SYSTEM STAINLESS STEEL SINGLE POINT FIXING SET

Stainless steel single point fixing for toughened safety glass panes

Designation	Description	ldent- No.	Colour	Glass thickness
All-glass system stainless steel single point fixing set	2 pieces, brushed, for wooden leaves and glass leaves 8-12 mm, including 4 Rampa sleeves (wood) and installation material for glass	127961	Stainless steel	8 - 12 mm

DOOR PULL HANDLE, CONFIGURED *

Push bar - round design for installation on glass leaves

Designation	Ident-No.	Colour
Door pull handle, configured *	127616	Stainless steel









* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.