

Product data sheet

Levolan 60 glass

ceiling installation



Sliding door fitting for 60 kg glass leafs and ceiling installation



AREAS OF APPLICATION

- For design-oriented interior sliding doors for living and office areas
- For all single- and multiple-leaf sliding doors
- Installation to the ceiling
- For attachment on the wall and ceiling (directly and concealed) as well as for glass installation
- Damped on one or both sides with Levolan 60 SoftStop
- Smooth running with Levolan 60 SoftStop makes it particularly well suited for doors in living and office spaces

PRODUCT FEATURES

- Design sliding door fitting system for glass doors with ESG (toughened safety glass) 8 to 12 mm as well as LSG up to 10.76 mm and up to 60 kg leaf weight
- Additional cover profile for aesthetically covering the back of the track
- Slim design with integrated door fitting technology
- Fully integrated in the track
- The Levolan Smart fix installation system means the use of assembly tools is reduced to a minimum - for quick and convenient installation
- Final assembly of the door fitting by simple clipping
- With damping on one or both sides for doors with up to 60 kg leaf weight, so that the door is quietly slowed down and moved automatically into the end position
- Tested for durability in accordance with DIN EN 1527 over 100,000 test cycles

TECHNICAL DATA

Productname

Levolan 60 glass ceiling installation

Levolan 60 glass ceiling installation



PART

COVER PROFILE FOR CEILING INSTALLATION LEVOLAN 60/120

Cover profile for Levolan 60/120 sliding door fitting



Designation	Description	Ident-No.	Colour
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145600	EV1
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145614	Stainless steel optic
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145613	Stainless steel optic
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	157983	EV1
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145598	EV1
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145615	Stainless steel optic
Cover profile for ceiling installation Levolan 60/120	bespoke configuration	145616	
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145599	EV1
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	157985	Stainless steel optic
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145611	EV1
Cover profile for ceiling installation Levolan 60/120	for covering the back side for ceiling mounting	145612	Stainless steel optic

LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Levolan 60 glass ceiling installation



Designation	Description	Ident-No.
LSG glass / metal glue 5x1 g *	for up to 5 sliding panels	133056

LEVOLAN 60 COMPLETE SET

Levolan sliding door fitting for leaf weights up to 60 kg



Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Levolan 60 complete set	For wall installation	147169	Stainless steel optic	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147166	EV1	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147167	Stainless steel optic	400 mm	840 mm
Levolan 60 complete set	For wall installation	147164	EV1	400 mm	840 mm
Levolan 60 complete set	For wall installation	147165	EV1	400 mm	1040 mm
Levolan 60 complete set	For wall installation	147168	Stainless steel optic	400 mm	1040 mm

ACCESSORIES

SPACER PROFILE FOR WALL CLEARANCE LEVOLAN 60 / 120

Spacer profile for wall installation of Levolan 60/120



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157993	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147571	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147557	EV1
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147559	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147572	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147558	EV1
Spacer profile for wall clearance Levolan 60 / 120	bespoke configuration	147573	
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157991	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147560	Stainless steel optic

Levolan 60 glass ceiling installation



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147556	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147555	EV1

LEVOLAN SOFTSTOPDUO SET, DAMPED ON BOTH SIDES, UP TO 100 KG

Levolan SoftStopDuo draw-in damping on both sides for leaf weights up to 100 kg



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan SoftStopDuo set, damped on both sides, up to 100 kg	for draw-in damping left & right, consisting of; 1 x double damping unit, 2 x spacers - Levolan 60 and 2 x spacers - Levolan 120 for cover panel bracket, 2 x adjustable triggers, can also be retrofitted - for Levolan 60 minimum leaf width 770 mm, for Levolan 120 minimum leaf width 1010 mm	146402	770 mm	1240 mm

LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side left version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping left, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146370	570 mm	1240 mm

Levolan 60 glass ceiling installation



LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side right version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping right, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146401	570 mm	1240 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.